LMDiffusion
Network & Electronic solutions
Add : Rue du Grand Champ 1, 5380 Fernelmont, Belgium
Call Tel : + 32 (0)495 861340 **GSM :** + 32 (0)495 861340
Website: http://www.lmdiffusion.be
E-mail: info@lmdiffusion.be

CCTV Camera Price List for Distributors IN € HTVA

New Products

Ver.: 201008A

Model No.	Specification	Chief Characteristic	Product Show
LPTAS	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PT Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★Lens: 4-9mm Manual Zoom Lens ★Size: Ø138x212mm Weight: 2.2Kg	
LPTASHQ	Color 1/3" SONY, 540TV Lines		
LPTASHL	Color 1/3" SONY, 540TV Lines Low Illumination		
LPTAXS	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: Ø138x212mm Weight: 2.2Kg	
LPTAXSHQ	Color 1/3" SONY, 540TV Lines		
LPTAXSHL	Color 1/3" SONY, 540TV Lines Low Illumination		
LPTMS	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PT Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★Lens: 4-9mm Manual Zoom Lens ★Size: Ø121x177mm Weight: 2Kg	
LPTMSHQ	Color 1/3" SONY, 540TV Lines		
LPTMSHL	Color 1/3" SONY, 540TV Lines Low Illumination		
LPTMXS	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: Ø121x177mm Weight: 2Kg	
LPTMXSHQ	Color 1/3" SONY, 540TV Lines		
LPTMXSHL	Color 1/3" SONY, 540TV Lines Low Illumination		
LPTES	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec ★Preset: 16 ★RS485, Pelco D/P supported ★Two brackets included (for Ceiling & Side mount) ★Lens: Board Lens 6mm ★Size: Ø138x266mm Weight: 2Kg	
LPTESHQ	Color 1/3" SONY, 540TV Lines		
LPTESHL	Color 1/3" SONY, 540TV Lines Low Illumination		

LPTEXS	**Color 1/3" SONY, 420TV Lines**	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec ★Preset: 16 ★RS485, Pelco D/P supported ★Two brackets included (for Ceiling & Side mount) ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: ∅138x266mm Weight: 2Kg	
LPTEXSHQ	**Color 1/3" SONY, 540TV Lines**		
LPTEXSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LPDRHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof Outdoor Dome Camera	
LPDRS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LPDRSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	**Outdoor design, Water resistance: IP66**	
LPDRSHQ	**Color 1/3" SONY, 540 TV Lines**	**3-Axis bracket built-in**	
LPDRSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	**Lens: 4-9mm Manual Zoom Lens**	
LPDRSHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Size: Ø138x212mm Weight: 2.2Kg	
LVDPHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof Dome Camera	
LVDPS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LVDPSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Auto White Balance(AWB)	
LVDPSHQ	**Color 1/3" SONY, 540 TV Lines**	3-Axis bracket built-in	
LVDPSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Lens:4-9mm Manual Zoom Lens	
LVDPSHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension: ¢ 118x 92(H) mm Weight:750g	
LVDPBHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof Dome Camera	
LVDPBS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LVDPBSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	3-Axis bracket built-in	
LVDPBSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens:4-9mm Manual Zoom Lens	
LVDPBSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	DC12V/AC24V double voltage add USD4	
LVDPBSHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension: ¢ 140x 120(H) mm Weight:1100g	
LIK24HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket	
LIK24S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢ 5X24PCS IR LED working distance:20M	
LIK24SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance:IP66 Cable built-in bracket	
LIK24SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 3.6mm/F2.0	
LIK24SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension:175(W) x124(H) x83(D)mm Weight:900g	

LIK40HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket	
LIK40S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢5X42PCS IR LED working distance: 40M	
LIK40SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance:IP66 Cable built-in bracket	
LIK40SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: CS Lens 6mm/F2.0	
LIK40SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension:228(W)x97(H)x82(D)mm Weight:1.2Kg	
LIKT40HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket	
LIKT40S	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LIKT40SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	IR LED: ¢5X42PCS IR LED working distance: 40M	
LIKT40SHQ	**Color 1/3" SONY, 540 TV Lines**	Water resistance:IP66 Cable built-in bracket	
LIKT40SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Lens: 4-9mm Manual Zoom Lens	
LIKT40SHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension:228(W)x97(H)x82(D)mm Weight:1.2Kg	
LIKT90HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket	
LIKT90S	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LIKT90SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	IR LED: ¢5X72PCS IR LED working distance: 60M	
LIKT90SHQ	**Color 1/3" SONY, 540 TV Lines**	Water resistance:IP66 Cable built-in bracket	
LIKT90SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Lens: 8-20mm Manual Zoom Lens	
LIKT90SHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension:295(W)x120(H)x103(D)mm Weight:1.4Kg	

Promotions

Model No.	Specification	Chief Characteristic	Product Show
LPDRHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof Outdoor Dome Camera SONY/SHARP Color CCD Outdoor design, Water resistance: IP66 3-Axis bracket built-in Lens: 4-9mm Manual Zoom Lens Size: Ø138x212mm Weight: 2.2Kg	
LPDRS	**Color 1/3" SONY, 420 TV Lines**		
LPDRSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIRDBHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof IR Dome Camera SONY/SHARP Color CCD IR LED: ¢5X24PCS IR distance: 20M Lens: Board Lens 3.6mm/F2.0 Dimension: ¢94 x 69(H) mm Weight:500g	
LIRDBS	**Color 1/3" SONY, 420 TV Lines**		
LIRDBSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIRDCHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof IR Dome Camera SONY/SHARP Color CCD IR LED: ¢5X36PCS IR distance: 30M Lens: 4-9mm Manual Zoom Lens Dimension: ¢131 x 93(H) mm Weight:850g	
LIRDCS	**Color 1/3" SONY, 420 TV Lines**		
LIRDCSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIXT40HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket SONY/SHARP Color CCD IR LED: ¢5X36PCS IR LED working distance: 30M Water resistance:IP66 Cable built-in bracket Lens: 4-9mm Manual Zoom Lens Dimension:256(W)x143(H)x86(D)mm Weight:2.3Kg	
LIXT40S	**Color 1/3" SONY, 420 TV Lines**		
LIXT40SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIK24HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket IR LED: ¢5X24PCS IR LED working distance:20M Water resistance: IP66 Cable built-in bracket Lens: Board Lens 3.6mm/F2.0 Dimension:175(W) x124(H) x83(D)mm Weight:900g	
LIK24S	**Color 1/3" SONY, 420 TV Lines**		
LIK24SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIK40HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket IR LED: ¢5X42PCS IR LED working distance: 40M Water resistance:IP66 Cable built-in bracket Lens: CS Lens 6mm/F2.0 Dimension:228(W)x97(H)x82(D)mm Weight:1.2Kg	
LIK40S	**Color 1/3" SONY, 420 TV Lines**		
LIK40SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIKT40HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket SONY/SHARP Color CCD IR LED: ¢5X42PCS IR LED working distance: 40M Water resistance: IP66 Cable built-in bracket Lens: 4-9mm Manual Zoom Lens Dimension:228(W)x97(H)x82(D)mm Weight:1.2Kg	
LIKT40S	**Color 1/3" SONY, 420 TV Lines**		
LIKT40SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		

LIKT90HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket SONY/SHARP Color CCD IR LED: ¢5X72PCS IR LED working distance: 60M Water resistance: IP66 Cable built-in bracket Lens: 8-20mm Manual Zoom Lens Dimension:295(W)x120(H)x103(D)mm Weight:1.4Kg	
LIKT90S	**Color 1/3" SONY, 420 TV Lines**		
LIKT90SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LICE24NHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket IR LED: ¢5X24PCS IR distance: 20M Lens: Board Lens 3.6mm/F2.0 Cable Build-in Bracket included Dimension:86(W) x60(H) x55(D)mm Weight:500g	
LICE24NS	**Color 1/3" SONY, 420 TV Lines**		
LICE24NSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIT40EHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera IR LED: ¢5X36PCS IR distance: 30M Lens: 4-9mm Manual Zoom Lens Cable Build-in Bracket included Dimension:200(W)x171(H)x83(D)mm Weight:2.0Kg	
LIT40ES	**Color 1/3" SONY, 420 TV Lines**		
LIT40ESL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIT90EHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera IR LED: ¢8X36PCS IR distance: 50M Lens: 4-9mm Manual Zoom Lens Cable Build-in Bracket included Dimension:240W)x186(H)x100(D)mm Weight:2.2Kg	
LIT90ES	**Color 1/3" SONY, 420 TV Lines**		
LIT90ESL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		

Dome Cameras

Model No.	Specification	Chief Characteristic	Product Show
LCDSHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Plastic Dome Camera SONY/SHARP Color CCD Auto White Balance(AWB) Lens: Board Lens 3.6mm/F2.0 Dimension: ¢88 x 58(H) mm Weight:250g	
LCDSS	**Color 1/3" SONY, 420 TV Lines**		
LCDSSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LCDSSHQ	**Color 1/3" SONY, 540TV Lines**		
LCDSSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LCDMHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Plastic Dome Camera SONY/SHARP Color CCD Auto White Balance(AWB) Lens: Board Lens 3.6mm/F2.0 Dimension: ¢118 x 74(H) mm Weight:350g	
LCDMS	**Color 1/3" SONY, 420 TV Lines**		
LCDMSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LCDMSHQ	**Color 1/3" SONY, 540 TV Lines**		
LCDMSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		

LCDRHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Plastic Dome Camera	
LCDRS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LCDRSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	3-Axis bracket built-in	
LCDRSHQ	**Color 1/3" SONY, 540TV Lines**	Lens: 3.6mm Board lens	
LCDRSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: ¢ 100 x 78(H) mm Weight:300g	
LCDHHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Plastic Dome Camera	
LCDHS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LCDHSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Auto White Balance(AWB)	
LCDHSHQ	**Color 1/3" SONY, 540 TV Lines**	3-Axis bracket built-in	
LCDHSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Lens:4-9mm Manual Zoom Lens	
LCDHSHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension: ¢ 118 x 106(H) mm Weight:600g	
LCDPHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Plastic Dome Camera	
LCDPS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LCDPSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	3-Axis bracket built-in	
LCDPSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 3.6mm/F2.0	
LCDPSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: ¢ 130 x 93(H) mm Weight:600g	
LCDMIR24HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Plastic IR Dome Camera	
LCDMIR24S	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LCDMIR24SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	IR LED: ¢ 5X24PCS IR LED working distance: 20M	
LCDMIR24SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 3.6mm/F2.0	
LCDMIR24SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: ¢ 118 x 74(H) mm Weight:350g	
LIRDPHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Plastic IR Dome Camera	
LIRDPS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LIRDPSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	IR LED: ¢ 5X24PCS IR LED working distance: 20M	
LIRDPSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 3.6mm/F2.0	
LIRDPSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: ¢ 94 x 69(H) mm Weight:300g	
LVDSHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof Dome Camera	
LVDSS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LVDSSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Auto White Balance(AWB)	
LVDSSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: 3.6mm Board lens	
LVDSSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: ¢ 108 x 69(H) mm Weight:600g	
LVDKHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof Dome Camera	
LVDKS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LVDKSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Auto White Balance(AWB)	
LVDKSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: 4-9mm Manual Zoom Lens	
LVDKSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimensio: ¢ 140 x 94(H) mm	
LVDKSHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Weight: 850g	

LVDPHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof Dome Camera	
LVDPS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LVDPSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Auto White Balance(AWB)	
LVDPSHQ	**Color 1/3" SONY, 540 TV Lines**	3-Axis bracket built-in	
LVDPSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Lens:4-9mm Manual Zoom Lens	
LVDPSHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension : ¢ 118x 98(H) mm Weight:750g	
LVDPBHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof Dome Camera	
LVDPBS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LVDPBSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	3-Axis bracket built-in	
LVDPBSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens:4-9mm Manual Zoom Lens	
LVDPBSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	DC12V/AC24V double voltage add USD4	
LVDPBSHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension : ¢ 140x 120(H) mm Weight:1100g	
LVDPXHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Auto Focus Vandalproof Dome Camera	
LVDPXS	**Color 1/3" SONY, 420 TV Lines**	RS485/Video Line control Auto Focus Lens 3-Axis bracket built-in	
LVDPXSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	4-9mm dynamic varifocal lens	
LVDPXSHQ	**Color 1/3" SONY, 540 TV Lines**	DC12V/AC24V double voltage add USD4	
LVDPXSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: ¢ 140x 120(H) mm Weight:1350g	
LVDLIR24HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof IR Dome Camera	
LVDLIR24S	**Color 1/3" SONY, 420 TV Lines**	3-Axis bracket built-in	
LVDLIR24SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	IR LED: ¢ 5X21PCS IR LED working distance: 20M	
LVDLIR24SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: 4-9mm Manual Zoom Lens	
LVDLIR24SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: ¢ 149 x 99(H) mm Weight:1.3kg	
LIRDBHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof IR Dome Camera HOT!	
LIRDBS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LIRDBSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	IR LED: ¢ 5X24PCS IR LED working distance: 20M	
LIRDBSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 3.6mm/F2.0	
LIRDBSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: ¢ 94 x 69(H) mm Weight:500g	

LIRDCHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof IR Dome Camera SONY/SHARP Color CCD Auto White Balance(AWB) IR LED: ¢5X36PCS IR LED working distance: 30M Lens: 4-9mm Manual Zoom Lens Dimension: ¢131 x 93(H) mm Weight:850g	HOT!
LIRDCS	**Color 1/3" SONY, 420 TV Lines**		
LIRDCSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIRDCSHQ	**Color 1/3" SONY, 540 TV Lines**		
LIRDCSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LIRDCSHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**		
LIRDEHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Vandalproof IR Dome Camera SONY/SHARP Color CCD IR LED: ¢5X24PCS IR LED working distance: 20M Lens: Board Lens 3.6mm/F2.0 Dimension: ¢94 x 69(H) mm Weight:450g	
LIRDES	**Color 1/3" SONY, 420 TV Lines**		
LIRDESL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIRDESHQ	**Color 1/3" SONY, 540 TV Lines**		
LIRDESHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LPDRHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	**Vandalproof Outdoor Dome Camera** SONY/SHARP Color CCD **Outdoor design, Water resistance: IP66** **3-Axis bracket built-in** **Lens: 4-9mm Manual Zoom Lens** Size: Ø138x212mm Weight: 2.2Kg	NEW!
LPDRS	**Color 1/3" SONY, 420 TV Lines**		
LPDRSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LPDRSHQ	**Color 1/3" SONY, 540 TV Lines**		
LPDRSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LPDRSHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**		
LPTAS	**Color 1/3" SONY, 420TV Lines**	★Vandalproof Mini PT Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★Lens: 4-9mm Manual Zoom Lens ★Size: Ø138x212mm Weight: 2.2Kg	
LPTASHQ	**Color 1/3" SONY, 540TV Lines**		
LPTASHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LPTAXS	**Color 1/3" SONY, 420TV Lines**	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: Ø138x212mm Weight: 2.2Kg	NEW!
LPTAXSHQ	**Color 1/3" SONY, 540TV Lines**		
LPTAXSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		

LPTMS	**Color 1/3" SONY, 420TV Lines**	★Vandalproof Mini PT Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★Lens: 4-9mm Manual Zoom Lens ★Size: Ø121x177mm Weight: 2Kg	NEW!
LPTMSHQ	**Color 1/3" SONY, 540TV Lines**		
LPTMSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LPTMXS	**Color 1/3" SONY, 420TV Lines**	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: Ø121x177mm Weight: 2Kg	NEW!
LPTMXSHQ	**Color 1/3" SONY, 540TV Lines**		
LPTMXSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LPTES	**Color 1/3" SONY, 420TV Lines**	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec ★Preset: 16 ★RS485, Pelco D/P supported ★Two brackets included (for Ceiling & Side mount) ★Lens: Board Lens 6mm ★Size: Ø138x266mm Weight: 2Kg	NEW!
LPTESHQ	**Color 1/3" SONY, 540TV Lines**		
LPTESHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LPTEXS	**Color 1/3" SONY, 420TV Lines**	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec ★Preset: 16 ★RS485, Pelco D/P supported ★Two brackets included (for Ceiling & Side mount) ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: Ø138x266mm Weight: 2Kg	NEW!
LPTEXSHQ	**Color 1/3" SONY, 540TV Lines**		
LPTEXSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LPT24HF	**Color 1/4" SHARP,420TV Lines**	★360 Degree Pan Tilt IR Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec ★Preset: 16 ★RS485, Pelco D/P supported ★IR LED: 24pcs, IR working distance:20M ★Lens: Board Lens 6mm/F2.0 ★Size: Ø138x142mm Weight: 1250g	
LPT24S	**Color 1/3" SONY, 420TV Lines**		
LPT24SHQ	**Color 1/3" SONY, 540TV Lines**		
LPT24SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		

LPT24XHF	**Color 1/4" SHARP,420TV Lines**	★360 Degree Pan Tilt IR Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90° Flip ★Pan Speed: Max 50°/sec ★Preset: 16 ★RS485, Pelco D/P supported ★IR LED: 24pcs, IR working distance:20M ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: Ø138x142mm Weight: 1250g	
LPT24XS	**Color 1/3" SONY, 420TV Lines**		
LPT24XSHQ	**Color 1/3" SONY, 540TV Lines**		
LPT24XSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		

Weatherproof IR Cameras

Model No.	Specification	Chief Characteristic	Product Show
LIXT40HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket	 
LIXT40S	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LIXT40SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	IR LED: ¢5X36PCS IR LED working distance: 30M	
LIXT40SHQ	**Color 1/3" SONY, 540 TV Lines**	Water resistance: IP66 Cable built-in bracket	
LIXT40SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Lens: 4-9mm Manual Zoom Lens	
LIXT40SHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension:256(W)x143(H)x86(D)mm Weight:2.3Kg	
LIXT90HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket	 
LIXT90S	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LIXT90SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	IR LED: ¢8X36PCS IR LED working distance: 50M	
LIXT90SHQ	**Color 1/3" SONY, 540 TV Lines**	Water resistance: IP66 Cable built-in bracket	
LIXT90SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Lens: 4-9mm Manual Zoom Lens, DC12V/AC24V double voltage add USD4	
LIXT90SHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension:259(W)x159(H)x104(D)mm Weight:2.5Kg	
LICE24NHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket	
LICE24NS	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢5X24PCS IR LED working distance:20M	
LICE24NSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66 Cable built-in bracket	
LICE24NSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 3.6mm/F2.0	
LICE24NSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension:86(W) x60(H) x55(D)mm Weight:500g	
LICE24HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket	
LICE24S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢5X24PCS IR LED working distance:20M	
LICE24SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66 Cable built-in bracket	
LICE24SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 3.6mm/F2.0	
LICE24SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension:100(W) x77(H) x77(D)mm Weight:700g	

LICE36HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket IR LED: ¢5X36PCS IR LED working distance: 30M Water resistance: IP66 Cable built-in bracket Lens: Board Lens 6mm/F2.0 Dimension :153(W)x97(H)x82(D)mm Weight:900g	
LICE36S	**Color 1/3" SONY, 420 TV Lines**		
LICE36SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LICE36SHQ	**Color 1/3" SONY, 540 TV Lines**		
LICE36SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LICE48HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera SONY/SHARP Color CCD IR LED: ¢5X48PCS IR LED working distance: 40M Water resistance: IP66 Cable built-in bracket Lens: Board Lens 8mm/F2.0 Dimension :153(W)x97(H)x82(D)mm Weight:900g	
LICE48S	**Color 1/3" SONY, 420 TV Lines**		
LICE48SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LICE48SHQ	**Color 1/3" SONY, 540 TV Lines**		
LICE48SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LICE48SHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**		
LICEB48HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera SONY/SHARP Color CCD IR LED: ¢5X48PCS IR LED working distance: 40M Water resistance: IP66 Cable built-in bracket Lens: Board Lens 8mm/F2.0 Dimension :200(W)x78(H)x82(D)mm Weight:1.0kg	
LICEB48S	**Color 1/3" SONY, 420 TV Lines**		
LICEB48SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LICEB48SHQ	**Color 1/3" SONY, 540 TV Lines**		
LICEB48SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LICEB48SHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**		
LIA40EHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera IR LED: ¢5X42PCS IR LED working distance: 40M Water resistance: IP66 Cable built-in bracket Lens: 4-9mm Manual Zoom Lens External lens adjusting, DC12V/AC24V double voltage add USD4 Dimension: 200(W)x171(H)x83(D)mm Weight:1.3Kg	
LIA40ES	**Color 1/3" SONY, 420 TV Lines**		
LIA40ESL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIA40ESHQ	**Color 1/3" SONY, 540 TV Lines**		
LIA40ESHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LIA40ESHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**		
LIA90EHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera IR LED: ¢5X72PCS IR LED working distance: 60M Water resistance: IP66 Cable built-in bracket Lens: 8-20mm Manual Zoom Lens External lens adjusting, DC12V/AC24V double voltage add USD4 Dimension:240W)x186(H)x100(D)mm Weight:1.5Kg	
LIA90ES	**Color 1/3" SONY, 420 TV Lines**		
LIA90ESL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LIA90ESHQ	**Color 1/3" SONY, 540 TV Lines**		
LIA90ESHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LIA90ESHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**		
LIXTA90S	**Color 1/3" SONY, 420 TV Lines**	Weatherproof IR camera with 3-Axis Bracket IR LED: ¢8X36PCS IR distance: 50M Water resistance: IP66 Cable built-in bracket	
LIXTA90SHQ	**Color 1/3" SONY, 540 TV Lines**	**Lens: 4-9mm Manual Zoom Auto Iris Lens** **Removable IR-CUT Light filter switch function** Dimension: 259(W)x159(H)x104(D)mm Weight:2.5Kg	

LIK24HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket
LIK24S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ✆5X24PCS IR LED working distance:20M
LIK24SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66 Cable built-in bracket
LIK24SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 3.6mm/F2.0
LIK24SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension:175(W) x124(H) x83(D)mm Weight:900g
LIK40HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket
LIK40S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ✆5X42PCS IR LED working distance: 40M
LIK40SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66 Cable built-in bracket
LIK40SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: CS Lens 6mm/F2.0
LIK40SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension:228(W)x97(H)x82(D)mm Weight:1.2Kg
LIKT40HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket
LIKT40S	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD
LIKT40SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	IR LED: ✆5X42PCS IR LED working distance: 40M
LIKT40SHQ	**Color 1/3" SONY, 540 TV Lines**	Water resistance: IP66 Cable built-in bracket
LIKT40SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Lens: 4-9mm Manual Zoom Lens
LIKT40SHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension:228(W)x97(H)x82(D)mm Weight:1.2Kg
LIKT90HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket
LIKT90S	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD
LIKT90SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	IR LED: ✆5X72PCS IR LED working distance: 60M
LIKT90SHQ	**Color 1/3" SONY, 540 TV Lines**	Water resistance: IP66 Cable built-in bracket
LIKT90SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Lens: 8-20mm Manual Zoom Lens
LIKT90SHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension:295(W)x120(H)x103(D)mm Weight:1.4Kg
LIT40EHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera
LIT40ES	**Color 1/3" SONY, 420 TV Lines**	IR LED: ✆5X36PCS IR LED working distance: 30M
LIT40ESL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66 Cable built-in bracket
LIT40ESHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: 4-9mm Manual Zoom Lens
LIT40ESHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	External lens adjusting, DC12V/AC24V double voltage add USD4
LIT40ESHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension :200(W)x171(H)x83(D)mm Weight:2.0Kg
LIT90EHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera
LIT90ES	**Color 1/3" SONY, 420 TV Lines**	IR LED: ✆8X36PCS IR LED working distance: 50M
LIT90ESL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66 Cable built-in bracket
LIT90ESHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: 4-9mm Manual Zoom Lens
LIT90ESHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	External lens adjusting, DC12V/AC24V double voltage add USD4
LIT90ESHD	**Color 1/3" SONY, 600TV Lines Low Illumination, WDR, OSD**	Dimension: 240W)x186(H)x100(D)mm Weight:2.2Kg

LIS100HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera	
LIS100S	**Color 1/3" SONY, 420 TV Lines**	IR LED: 12PCS IR LED working distance: 100M	
LIS100SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66 Cable built-in bracket	
LIS100SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: CS Lens 16mm/F1.6	
LIS100SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: 275(W)x186(H)x123(D)mm Weight:2.6Kg	
LIR60HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera	
LIR60S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢8X36PCS IR LED working distance: 50M	
LIR60SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66	
LIR60SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: CS Lens 8mm/F2.0	
LIR60SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: 175(W)x174(H)x95(D)mm Weight:1.1Kg	
LIS48HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera	
LIS48S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢5X48PCS IR LED working distance: 40M	
LIS48SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66	
LIS48SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 6mm/F2.0	
LIS48SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: 175(W) x124(H) x83(D)mm Weight:900g	
LIS36HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera	
LIS36S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢5X36PCS IR LED working distance: 30M	
LIS36SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66	
LIS36SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 6mm/F2.0	
LIS36SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: 175(W) x124(H) x83(D)mm Weight:900g	
LIC30HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket	
LIC30S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢5X30PCS IR LED working distance:25M	
LIC30SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66 Cable built-in bracket	
LIC30SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 3.6mm/F2.0	
LIC30SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: 162(W) x72(H) x69(D)mm Weight:850g	
LIC48HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera with 3-Axis Bracket	
LIC48S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢5X48PCS IR LED working distance:40M	
LIC48SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66 Cable built-in bracket	
LIC48SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: Board Lens 6mm/F2.0	
LIC48SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension: 215(W) x85(H) x78(D)mm Weight:1.1kg	
LIC60HF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Weatherproof IR camera	
LIC60S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢8X36PCS IR LED working distance: 50M	
LIC60SL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Water resistance: IP66 **Build in auto temperature control**	
LIC60SHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: 5-15mm Manual Zoom Lens	
LIC60SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension:230(W)x180(H)x115(D)mm Weight:2.5Kg	
LIXTX90S	**Color 1/3" SONY, 420 TV Lines**	Weatherproof IR camera with 3-Axis Bracket IR LED: ¢8X36PCS IR LED working distance: 50M	
LIXTX90SHQ	**Color 1/3" SONY, 540 TV Lines**	Water resistance: IP66 Cable built-in bracket RS485/Video Line control Auto Focus Lens 4-9mm dynamic varifocal lens(standard) 5-15mm dynamic varifocal lens (Optional)	NEW!
LIXTX90SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension:259(W)x159(H)x104(D)mm Weight:2.5Kg	

Box Cameras

Model No.	Specification	Chief Characteristic	Product Show
LBCKS	**Color 1/3" SONY, 420 TV Lines**	Standard Box Camera	
LBCKSHQ	**Color 1/3" SONY, 540TV Lines**	Iris control:DC / VIDEO	
LBCKSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension:110(W)x45(H)x55(D)mm Weight:600g	

Mini DVR

Model No.	Specification	Chief Characteristic	Product Show
LSMDS06	**Mini DVR Camera support 32G SD card, bulid-in Lithium battery support 6 hours continuous video recording, with alarm siren**	★Motion & PIR detection ★Built-in SD card slot ★8G SD card included ★One alarm speaker connection port ★Automatic Photo/AVI video recording ★Recording video & jpeg with time & date stamptly ★Records events successively, overwriting old data when the Memory Card is full ★Weight: 1.1kg	

All In One Cameras

Model No.	Specification	Chief Characteristic	Product Show
LX22S	**Color 1/4" SONY, 420 TV Lines** **Minimum Illumination: 0.1Lux**	22X optical zoom lens F1.6 to F3.7, f=3.6 to 79.2mm Dimension:60(W)*60.4(H)*103(D)mm Weight:450g	
LX27S	**Color 1/4" SONY, 420 TV Lines** **Minimum Illumination: 0.1Lux**	27X optical zoom lens F1.6 to F3.7, f=3.6 to 97.2mm Dimension:60(W)*60.4(H)*103(D)mm Weight:450g	
LX220S	**Color 1/4" SONY, 420 TV Lines** **Minimum Illumination: 0.01Lux**	22X optical zoom lens with 10X digital zoom F1.6 to F3.7, f=3.9 to 85.8mm Dimension:60(W)*60.4(H)*103(D)mm Weight:450g	
LX220SH	**Color 1/4" SONY, 480 TV Lines** **Minimum Illumination: 0.01Lux**		
LX270S	**Color 1/4" SONY, 420 TV Lines** **Minimum Illumination: 0.01Lux**	27X optical zoom lens with 10X digital zoom F1.6 to F3.7, f=3.6 to 97.2mm Dimension:60(W)*60.4(H)*103(D)mm Weight:550g	
LX270SH	**Color 1/4" SONY, 480 TV Lines** **Minimum Illumination: 0.01Lux**		

Miniature Cameras

Model No.	Specification	Chief Characteristic	Product Show
LMCM25H	**Color 1/3" SHARP, 420 TV Lines**	Lens:3.7mm Taper Pinhole Lens (optional)	
LMCM25S	**Color 1/3" SONY, 420 TV Lines**	Dimension:25(W)x10(H)x25(D)mm Weight:120g	
LBWBSF	**Color 1/4" SONY, 420 TV Lines**	Lens:3.6mm Board Lens	
LBWBS	**Color 1/3" SONY, 420 TV Lines**	Dimension: ¢ 20 x 62(H) mm Weight:300g	
LBWASF	**Color 1/4" SONY, 420 TV Lines**	Lens:3.6mm Board Lens	
LBWAS	**Color 1/3" SONY, 420 TV Lines**	Dimension: ¢ 20 x 62(H) mm Weight:300g	
LBPBSF	**Color 1/4" SONY, 420 TV Lines**	Lens:3.7mm Taper Pinhole Lens	
LBPBS	**Color 1/3" SONY, 420 TV Lines**	Dimension: ¢ 20 x 62(H) mm Weight:250g	

Spy Cameras

Model No.	Specification	Chief Characteristic	Product Show
LUGHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	UFO Shape Camera	
LUGS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LUGSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Auto White Balance(AWB)	
LUGSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: 3.6mm Board lens	
LUGSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension : ¢ 75 x 74(H) mm Weight:300g	
LUFHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	UFO Shape Camera	
LUFS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LUFSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Auto White Balance(AWB)	
LUFSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: 3.6mm Board lens	
LUFSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension : ¢ 86 x 58(H) mm Weight:350g	

LUFBHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	UFO Shape Camera	
LUFBS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LUFBSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Auto White Balance(AWB)	
LUFBSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: 3.7mm Taper Pinhole Lens	
LUFBSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension : ∅86 x 53(H) mm Weight:350g	
LSDCHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Smoke Detector Camera	
LSDCS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LSDCSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Auto White Balance(AWB)	
LSDCSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens:3.6mm Board Lens	
LSDCSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension : ∅119 x 56(H) mm Weight:300g	
LPRCHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	PIR Spy Camera	
LPRCS	**Color 1/3" SONY, 420 TV Lines**	SONY/SHARP Color CCD	
LPRCSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**	Auto White Balance(AWB)	
LPRCSHQ	**Color 1/3" SONY, 540 TV Lines**	Lens: 3.7mm Taper Pinhole Lens	
LPRCSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**	Dimension :70(W) x40(H) x119(D)mm Weight:350g	

PTZ Camera & Auto

Model No.	Specification	Chief Characteristic	Product Show
LPTAS	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PT Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★Lens: 4-9mm Manual Zoom Lens ★Size: Ø138x212mm Weight: 2.2Kg	NEW!
LPTASHQ	Color 1/3" SONY, 540TV Lines		
LPTASHL	Color 1/3" SONY, 540TV Lines Low Illumination		
LPTAXS	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: Ø138x212mm; Weight: 2.2Kg	NEW!
LPTAXSHQ	Color 1/3" SONY, 540TV Lines		
LPTAXSHL	Color 1/3" SONY, 540TV Lines Low Illumination		
LPTMS	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PT Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★Lens: 4-9mm Manual Zoom Lens ★Size: Ø121x177mm Weight: 2Kg	NEW!
LPTMSHQ	Color 1/3" SONY, 540TV Lines		
LPTMSHL	Color 1/3" SONY, 540TV Lines Low Illumination		
LPTMXS	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec Preset: 16 ★Weatherproof Outdoor IP66 ★RS485, Pelco D/P supported ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: Ø121x177mm Weight: 2Kg	NEW!
LPTMXSHQ	Color 1/3" SONY, 540TV Lines		
LPTMXSHL	Color 1/3" SONY, 540TV Lines Low Illumination		
LPTES	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec ★Preset: 16 ★RS485, Pelco D/P supported ★Two brackets included (for Ceiling & Side mount) ★Lens: Board Lens 6mm ★Size: Ø138x266mm Weight: 2Kg	NEW!
LPTESHQ	Color 1/3" SONY, 540TV Lines		
LPTESHL	Color 1/3" SONY, 540TV Lines Low Illumination		
LPTEXS	Color 1/3" SONY, 420TV Lines	★Vandalproof Mini PTZ Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec ★Preset: 16 ★RS485, Pelco D/P supported ★Two brackets included (for Ceiling & Side mount) ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: Ø138x266mm Weight: 2Kg	NEW!
LPTEXSHQ	Color 1/3" SONY, 540TV Lines		
LPTEXSHL	Color 1/3" SONY, 540TV Lines Low Illumination		

LPT24HF	**Color 1/4" SHARP,420TV Lines**	★360 Degree Pan Tilt IR Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec ★Preset: 16 ★RS485, Pelco D/P supported ★IR LED: 24pcs, IR working distance:20M ★Lens: Board Lens 6mm/F2.0 ★Size: Ø138x142mm Weight: 1250g	
LPT24S	**Color 1/3" SONY, 420TV Lines**		
LPT24SHQ	**Color 1/3" SONY, 540TV Lines**		
LPT24SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LPT24XHF	**Color 1/4" SHARP,420TV Lines**	★360 Degree Pan Tilt IR Speed Dome camera ★Pan range: 0°~360°Continue (Not 355°) ★Tilt range: 0°~90°Flip ★Pan Speed: Max 50°/sec ★Preset: 16 ★RS485, Pelco D/P supported ★IR LED: 24pcs, IR working distance:20M ★4-9mm dynamic varifocal lens (standard) ★5-15mm dynamic varifocal lens (optional) ★Size: Ø138x142mm; Weight: 1250g	
LPT24XS	**Color 1/3" SONY, 420TV Lines**		
LPT24XSHQ	**Color 1/3" SONY, 540TV Lines**		
LPT24XSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LVDPXHF	**Color 1/4" SHARP,420 TV Lines Low Illumination**	Auto Focus Vandalproof Dome Camera RS485/Video Line control Auto Focus Lens , 3-Axis bracket built-in 4-9mm dynamic varifocal lens (standard) DC12V/AC24V double voltage add USD5 Dimension: ✆140 x 120(H) mm Weight:1350g	
LVDPXS	**Color 1/3" SONY, 420 TV Lines**		
LVDPXSL	**Color 1/3" SONY, 420 TV Lines Low Illumination**		
LVDPXSHQ	**Color 1/3" SONY, 540 TV Lines**		
LVDPXSHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
LIXTX90S	**Color 1/3" SONY, 420 TV Lines**	Weatherproof IR camera with 3-Axis Bracket IR LED: ✆8X36PCS IR LED working distance: 50M Water resistance:IP66 Cable built-in bracket RS485/Video Line control Auto Focus Lens 4-9mm dynamic varifocal lens(standard) 5-15mm dynamic varifocal lens (Optional) Dimension:259(W)x159(H)x104(D)mm Weight:2.5Kg	
LIXTX90SHQ	**Color 1/3" SONY, 540 TV Lines**		
LIXTX90SHL	**Color 1/3" SONY, 540TV Lines Low Illumination**		
SDK24	**Full function PTZ contronller Special design for PTZ Cameras**	★Wireless PTZ controller ★IR remote controler: Support 99pcs cameras ★RS-485 communication Pelco D/P support. ★Baud rate: 2400,4800 and 9600Bps ★Wireless distance: Max.20m ★Weight: 350g	

IP / Network Camer

Model No.	Specification	Chief Characteristic	Product Show
LNIC60S	**Color 1/3" SONY, 420 TV Lines**	IR LED: ¢ 8X36PCS IR working distance: 50M Lens: CS Lens 8mm/F2.0 Water resistance: IP66 MPEG-4 Compression Support Client software, IE, IPhone Romote View Support D1 Resolution Image Dimension:230(W) x180(H) x115(D)mm Weight:2.5kg	
LNIC60SHQ	**Color 1/3" SONY, 540 TV Lines**		
LNBIR24S	**Color 1/3" SONY, 420 TV Lines**	Constant Speed Dome IR & IP Camera With Pre-position IR LED: ¢ 5 x 24PCS IR working distance : 20M Lens: Board Lens 6mm/F2.0 Support D1 Resolution Image MPEG-4 Compression Support Client software, IE, IPhone Remote View Remote snapshot and video recording Dimension: ¢ 131 x 96mm Weight:1.3kg	
LNBIR24SHQ	**Color 1/3" SONY, 540 TV Lines**		

Price Terms:	**En € HTVA Hors frais de ports**
Attention:	**The Unit price fluctuates according to the change of parameters and market. And the price above is not including the delivery charge and other expenses**